



## BP Exterior Primer



**Product composition and usage:** BP Exterior Primer is a specially formulated value for money acrylic primer ideal for places experiencing dry climate and low rain fall. It may be applied on plasters, concrete and other masonry surfaces. The masonry surfaces should be fully cured, dry and free from loose materials.

**USP:** BP Exterior Primer may be applied on plasters, concrete and other masonry surfaces. The masonry surfaces should fully cured, dry and free from loose materials. Ensure that the surface to be painted is not exposed to continuous seepage of water or prone to efflorescence.

**Safety features:** Non-flammable

### DIRECTIONS FOR USE

**Surface preparation:** Remove paint, dirt, loose particles from the surface to be painted using wire mesh. Fill up minor cracks with crack-seal putty. Cracks which are larger than 5mm should to be filled with cement work. Let the surface dry completely. Check moisture content of the substrate. It should be below 12% for superior performance of the primer.

### COVERAGE\*

All on 1 coat primed surface	No. of coats	New surface
By brush/spray application	1 coat	90 - 100 sq ft

### RECOMMENDED SURFACES

Masonry surfaces,  
asbestos surfaces,  
brick work

\*It depends on many factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc. The coverage mentioned is under ideal conditions and will vary depending on site conditions. Coverage on different surfaces takes into account of co-efficient as per IS-1200.

### PACKS

Non ColorBank	Colour	Bases (ColorBank)
1 ltr, 4 ltr, 10 ltr 20 ltr	White only	NA

## TECHNICAL DATA

1	<b>Recommended Thinner</b>	Potable water
2	<b>Method of Application</b>	Spray, Brush or Roller after suitable dilution
3	<b>Recommended Dilution</b>	Dilute 1 ltr of primer with upto 1 ltr of water depending on required consistency.
4	<b>Drying Time</b>	SD: 15 minutes HD: 6-8 hours
5	<b>Number of Coats Required</b>	1 (Apply 1 extra coat if required)

6	<b>Gloss/Sheen</b>	Matt, no sheen
7	<b>Flash Point</b>	Non-flammable as it is water-based product
8	<b>Stability of Thinned Paint</b>	Use within 24 hours
9	<b>Shelf Life</b>	2 years from date of manufacturing in unopened containers kept in cool, dry place away from sunlight.
10	<b>VOC</b>	30 - 35 gm/ltr
11	<b>Certification</b>	IS:109/1968
12	<b>Safety Data</b>	Refer MSDS

### POINTS TO NOTE

- Shake well before use and do not over dilute
- Strain the material through a fine sieve before use
- Keep the container tightly closed to prevent drying
- Please keep out of reach of children and away from foodstuff
- In case of contact with eyes, wash immediately with water and seek medical advice

### SPECIAL NOTE

Before painting the following things should be checked thoroughly:

1. Moisture content of the wall (Ideal condition - below 12%)
2. pH value of the wall surface (Ideal condition - between 7-11)

If these are violated, owner will be responsible.

\*As per test conducted at Berger R&D

Version No: BPP2/02/2017. Please note that this data sheet supersedes all previous versions.

### BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | CONSUMER RELATIONS MANAGER Ph: 1800-103-6030  
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com