



# LUXOL 7 in 1

## ENAMEL



### Product Attributes



**Finish**  
Super Gloss finish

**Superior Coverage**



**Rust Resistant**

**Durability**  
Paint film has good durability



**Rust Resistant**

**Superior Coverage**



**Rust Resistant**

**Superior Coverage**



**Green Pro Certified**  
Validates our effort in striving towards cleaner, more sustainable future


### Product Description

Berger Luxol 7 in 1 Enamel is a quick drying, super gloss, lead/chrome-free anti-corrosive PU enamel for metal, wood and masonry surfaces. It is easy to apply and offers excellent gloss and gloss retention.

### Recommended Use

Applicable for both interior and exterior surfaces- metal, wood and masonry surfaces. 2 coats of Luxol QD 1K Epoxy Primer + 2 coats of Luxol 7 IN 1.

### Colour Range



12 READY SHADES  
3 BASES P0, W2, W3  
over 1500 shades

### Finish

- VERY HIGH
- HIGH
- SOFT SHEEN
- SUPER GLOSS** ✓

Super Gloss

### Recommended Dilution



Can be diluted with Berger T-12 solvent with 8-10% dilution (V/V) and Thinner 800

### Drying Time at 60% RH, 25° C



**Sd:** 1 Hour  
**Hd:** 24 Hours

### Coverage



110-130 sq.ft

### Application Method



Brush & Spray

### Gloss / Sheen Level



High Gloss

### Flash Point



Solvent- based paint, flammable

# LUXOL 7 in 1

## ENAMEL



### Packs



**Stability of Used Paint**  
Use within 24 hours

### Surface Preparation



Remove all dirt, loose paint, flakes using wire brush or sand paper.



Cover fine cracks with putty, large cracks may need cement work.



Allow sufficient time for the putty/cement work to dry.

### Priming



Recommended primers- Walls- BP Cement Primer ST, Ferrous Surface or Galvanized Steel - Luxol QD 1K Epoxy primer Wood- Parrot Wood Primer.

### Directions for Application



**Topcoat:**  
Apply 2 coats of 7 in 1 Luxol QD Super Gloss PU Enamel with recommended dilution ratio as finish coat. Apply second coat within 1 & 1/2 hours or after 36 hours of applying the first coat.

### Points to Note

Minimum two coats of primer and top coat are required

### Precautions

- Stir well and strain before use.
- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- Do not over-thin. Do not over-extend the brush.
- Tint using Berger Paints machine colourants only
- Mix the tinted shade in gyo shaker before use for uniform mixing

Version No: BPP1/01/2020. Please note that this data sheet supersedes all previous versions.

### BERGER PAINTS INDIA LIMITED

**Berger House**, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030  
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com