

# SILK GlamArt VINTAGE

# SILK GlamArt



## Drying Time



**Surface dry:** 4-6 hours  
**Hard dry:** Min 8-12 hours

## Dilution Ratio



No dilution for design application  
(READY TO USE)

## Product Description

Silk GlamArt Vintage finish is a ready to use special effects material that can be used to create a variety of textured effects on interior walls. Different types of designs such as DENIM, SPRINKLE, ARTISTIC etc. can be created using various application techniques.

## Usage Areas

Interior Puttied/POP/Wooden surfaces with proper surface preparation.

## Directions for Application

### Surface Preparation:



#### On Previously Painted Surfaces:

Strip all the old paint from the surface and wipe clean. Sand it down with sand paper 80/100 and wipe clean. Apply the first coat of primer and let it dry for 6 to 8 hours. Smoothen the surface by applying thin coats of Happy wall putty to fill in all the undulations. Let the putty to dry overnight. Sand the surface again, with sand paper 200/220, and wipe clean. Apply the second coat of primer and let it dry for 6-8 hours. Sand the surface with sand paper 320 and wipe clean.



#### On Fresh/New Surfaces:

Strip all the loose particles from the surface via scraping and wipe down. Wash the surface with water and let it dry. After this follow the steps recommended for previously painted surfaces.



#### Recommended undercoats for walls or plastered surfaces:

Primers: BP Cement Primer W/T, alkali resistant.  
Putty: Happy wall putty

#### Recommended undercoats for wooden surfaces:

Primer: Wood Primer (first coat) followed by Happy wall putty & sanding followed by BP Cement primer W/T alkali resistant.



#### Design Application:

Tint the material to get the desired shade and use a brush/ trowel to apply it directly on the previously prepared surface, without dilution. Use the tools and materials specified in the recommended manner to create the design of choice on the wall.

## Points To Note:

- Stir well before use.
- Do not apply when ambient temperature is below 100°C.
- Recoat and drying of paint are tested at 30±2°C and 60-65% RH. These may vary under different conditions.
- Fire Hazard Class: Non-Flammable.
- Tint with Berger Paints universal colorants and only tint shades on offer.
- Keep the container tightly closed in cool and dry place.
- Please keep it out of reach of children and away from foodstuff.
- In case of contact with eyes, wash immediately with water and seek medical advice.
- For safety measures, refer to MSDS.

Version No: BPP1/03/2022. Please note that this data sheet supersedes all previous versions.

## BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030  
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com