

# SILK GLAMOR

## LUXURY INTERIOR EMULSION



### Product Attributes



Water repellent

Flexible enough to cover hair-cracks



High opacity

High coverage



Low smell

### Product Description

Silk Glamor Luxury Emulsion is an interior wall paint designed to give your walls a durable premium, rich appearance. It is formulated with tailor-made 100% acrylic emulsion that retains the fresh glossy new look for a longer period. The product is free of added APEO, formaldehyde and is low on VOC.

Silk Glow comes in a range of shades to choose from which can give a unique premium look to the interiors.

#### VOC



30-35 gm/lt

#### Dilution Ratio



**Brush :** 40-50% by volume.

**Roller :** 35-40% by volume.

Deep shades from N base to be applied without dilution

#### Application Tools



Brush/ Roller/ Auto-roller

#### Coverage



150-170 sqft/lt/2 coats depending on shade, quality of surface preparation and application condition

#### Drying Time



**SD:** 15-25 min at 60% RH, 25°C  
**HD:** 6-8 hours

#### Gloss/ Sheen



60° = 13-15; 85° = 45-55 (depending on shade, measured as per standard test method)

#### Flash Point



water based paint, hence non-flammable

# SILK GLAMOR

## LUXURY INTERIOR EMULSION



**Fire Hazard Class**  
Non- flammable



**Stability of used paint**  
use within 24 hours

### Areas of application

Plastered surfaces, concrete walls, fibre board, asbestos, gypsum board and false ceiling

### APPLICATION DETAILS



#### Surface Preparation

Remove all dirt, loose paint, flakes using wire mesh. Cover fine cracks with putty, large cracks may need cement work. Allow sufficient time for the putty/cement work to dry.



#### Priming

Apply one coat of BP Cement Primer/ Seal-O-Prime suitably diluted and dry it overnight.



#### Top Coat

Mix well. Dilute with potable water and apply with brush or roller. Allow it to dry for at least 6-8 hours or overnight depending ambient temperature, humidity and surface conditions. Apply second coat only when the first coat is dry.  
**DO NOT OVERTHIN. DO NOT APPLY WHEN AMBIENT TEMPERATURE IS BELOW 10°C OR MORE THAN 40°C**

### SAFETY DATA

Refer MSDS

### ADDITIONAL INFORMATION

- No added lead, Chromium (VI), Mercury
- No added APEO, formaldehyde and ammonia

Version No: BPP1/07/2023. Please note that this data sheet supersedes all previous versions.

### BERGER PAINTS INDIA LIMITED

**Berger House**, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030  
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: [consumerfeedback@bergerindia.com](mailto:consumerfeedback@bergerindia.com) | [www.bergerpaints.com](http://www.bergerpaints.com)