



NIPPON PAINT

MULTI-PURPOSE SOLVENT PRIMER



Nippon Paint Multi-purpose solvent primer is a solvent-based undercoat for different types of Wood, POP, gypsum and cement surfaces.

GREEN ASSURED



PRODUCT FEATURES



Lead-free

Paints that does not contain heavy metals are safe to use at home and environment friendly too.



Where To use: Can be used on priming plastered walls, asbestos, brick work, concrete etc.



NIPPON PAINT

MULTI-PURPOSE SOLVENT PRIMER

TECHNICAL DETAILS

Bases	:	Nippon Paint Multi-purpose primer white
Colour Range	:	White
Finish	:	Matt
Dry Time	:	Touch Dry:1-2 Hrs Re coating: 6-7 Hrs
Gloss level	:	Matt
Clean solvent	:	Mineral Turpentine Oil (MTO) / General Purpose Thinner
Stability of diluted paint	:	24 Hours
Shelf life:	:	2 Years from the date of manufacture in original tightly closed containers .
Dilution	:	10% Dilution With Mineral Turpentine Oil (MTO) / General Purpose Thinner

Coverage:



MULTI-PURPOSE SOLVENT PRIMER

12.08 - 14.86 sq.mt./litre

(Actual coverage is depends on the substrate conditions and surface porosity and method of application.)

HOW TO APPLY

Surface Preparation:




Remove flakes of old paint or powdery residues by sanding using an emery paper. Surface must be free from dirt, grease, oil and other foreign substances.

Application:

- Brush:** Dilute the paint upto 10% by volume using Mineral turpentine / general purpose thinner
- Roller:** Dilute the paint upto 15-20% by volume using Mineral turpentine / general purpose thinner(may cause gloss reduction)
- Conventional Spray:** Dilute that paint upto 15-20 % by volume using Mineral turpentine / general purpose thinner

Process:



Primer
Nippon Paint
Multi Purpose Solvent Primer

Apply 1 coat

Allow it to dry for 6-8 hours

SAFETY AND ENVIRONMENT

During Painting:

Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.

Cleaning:

Wash all the tools with Mineral Turpentine Oil (MTO) / General Purpose Thinner immediately after application.

Safety Instructions:

In the case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint for skin, use soap and water or appropriate cleanser. In the event of spillage, contain and collect spilt paint by using sand or earth.

Precautions:

Avoid painting when the temperature is below 10°C. Painting is not recommended if the moisture content and alkalinity of the walls is high. Moisture content of the walls should be below 10% (measured by Protimeter) and alkalinity of the wall should be below pH-9. Relative humidity should be below 85%. Painting on a newly plastered wall is recommended after 12 weeks of curing.

Storage:

Store paint in a cool, dry and well ventilated place away from heat sources, flammables or direct sunlight. Keep container tightly closed in a secure, upright position. Do not store near food, drink or animal feed. Keep out of reach of children. Do not dispose of unwanted paint into drains, water sources or open sewers. To dispose safely, pour unwanted paint onto old newspapers and let dry before placing in a proper waste receptacle

Disposal Information:

Disposal of any paint waste & containers in accordance with applicable Environment (Protection) Act 1986 under the Hazardous Wastes (Management & Handling) rules 1989.

Environment:

Does not contain any added lead, mercury or chromium compounds.
Lead content does not exceed 90 parts per million.

Note: Do not Keep unpainted for more than 15 days.

