



**NIPPON  
PAINT**

## STYLFIX-TILE ADHESIVE

Polymer Modified Cement-based Tile Adhesive

Walltron Stylfix Tile Adhesive is a single component cement-based polymer modified adhesive for fixing tiles on the floors as well as walls in interior/exterior areas.

### GREEN ASSURED



SAFER FOR YOUR HEALTH



Indian Green Building Council  
FOUNDING MEMBER



### PRODUCT FEATURES



**Ease of Application**



**Superior Durability**



**Quick Curing**



**Optimal Setting Time**



**Superior Adhesion**

### APPLICATION AREA:

For fixing tiles on the floors as well as walls in interior/exterior areas.

Types of tiles:

- Ceramic tiles
- Vitrified tiles
- Marble
- Granites



- Ease of application
- Superior adhesion
- Superior durability
- Quick curing
- Optimal setting time

30 Kg



**NIPPON  
PAINT**

**STYLFIX-TILE ADHESIVE**  
Polymer Modified Cement-based Tile Adhesive

## TECHNICAL DETAILS

Appearance	Free-flowing grey powder
Pot life	30 min

## Coverage:



### WALLTRON STYLFIX-TILE ADHESIVE

2-3 sq.ft/kg for 3mm thickness.

## HOW TO APPLY

### Surface Preparation:



Surface to be tiled must be clean, free from contamination and in Saturated Surface Dry (SSD) condition.

### Precautions:

- Always add tile adhesive to water and not water to the tile adhesive.
- Tiles can be fixed within 15 minutes of tile adhesive application.
- Tiles can be adjusted up to 10 minutes after fixing.
- Leave the surface for 24 hours for drying.
- Hand mixing is recommended only for small quantities.
- Should not be used on painted, metal surfaces, ply & gypsum boards.
- Use the mix within 30 minutes.
- Nippon Paint Stylfix can be used for laying marble and granites on horizontal surfaces only.

### Application:

- Mix Nippon Paint Stylfix into clean water in the ratio 3-3.5 parts of powder, 1 part of water and stir to get a lump-free mix.
- Allow it to stand for 5 minutes.
- Spread Nippon Paint Stylfix on the surface using a trowel (Spread the quantity of tile adhesive which can be tiled in 15 mins) and comb using a notched trowel of appropriate depth.
- Press the tile firmly into position with a slight twisting action to maximize contact area.
- Leave adequate joints between the tiles by using spacers.

## SAFETY AND ENVIRONMENT

### During Application:

Always work in a well-ventilated area. Wear appropriate attire, especially gloves, eye protection and mask. Avoid contact with skin as it may cause irritation.

### Cleaning:

Wash all tools with clean water immediately after application.

### Safety Instructions:

In case of eye contact rinse immediately with water and seek immediate medical treatment. To remove Putty from skin, use soap and water or appropriate cleanser. In the event of spillage, contain and collect split putty by using sand or earth.

### Storage:

Store Tile adhesive in a cool dry and well ventilated place away from heat sources, flammables or direct sun light. Keep the loose bags with mouth tied tightly with string after taking the material to prevent lump formation. Do not store near food, drinks or animal feed. Keep out of reach of children. Safety datasheets will be made available to professional users upon request

### Shelf Life:

Best before 6 months from date of manufacturing in unopened original packing when stored in dry condition.

