



NSeal CRACK FILL PASTE

Walltron NSeal crack fill paste is an easy to apply, single pack, ready-to-use, water-resistant, flexible material for filling cracks in plastered surfaces. It has excellent bonding, durability, and aesthetic appearance. It is composed of high-quality and weather durable acrylic emulsion polymer, carefully selected fillers, fibres and additives for interior as well as exterior surfaces.

GREEN ASSURED



PRODUCT FEATURES



Ready to use paste



Ease of Application



Flexible



Eco friendly



Non-staining



Excellent Bonding



Durable



Non toxic

APPLICATION AREA:

It is recommended to use for both interior and exterior cracks on horizontal & vertical surfaces upto 5mm thickness





NIPPON PAINT

NSeal CRACK FILL PASTE

TECHNICAL DETAILS

Appearance & consistency	Smooth, thick paste contains fibers
Pot life	30 min
Colour	White - Off White
Sp. Gravity @ 30°C	1.40 +/-0.04
% Solids (120°C / 1 hour)	75.00 - 80.00
Water resistance	Excellent

Coverage:



WALLTRON NSEAL CRACK FILL PASTE

Approx 25-30 running m/kg

Coverage depends on size of the crack.

HOW TO APPLY

Surface Preparation:

- Surface must be free from dust, oil, grease, and loose particles, etc.
- Moisten the surface before applying Walltron NSeal crack fill paste.
- Hairline cracks must be widened up to 1 mm minimum & into a V shaped groove by using a scraper or cutter prior to filling.
- Remove existing POP or painter's putty must be removed till plaster surface is exposed.
- Treat porous surfaces with any acrylic primer and then fill the NSeal crack fill paste when the surface is tacky.

Mixing & Application:

- Press Walltron NSeal crack fill paste firmly into the crack with a spatula or putty knife and level with the surface.
- Care must be taken to avoid formation of cavities or bubbles during application
- Allow it to set for 24 hours and then apply another coat of Walltron NSeal crack fill paste.
- Further application of POP or painter's putty can be taken up once it is fully dry.
- For best results allow crack filler to cure for 7 days.
- Apply NSeal crack fill paste at least 3cm on either side of the crack for better adhesion.

Precautions and Limitations:

- Recommended only for filling static cracks on walls, not for filling structural joints.
- Do not mix excess water.
- Not for cracks in POP or painter's putty
- For application below 10 °C, drying time will be delayed
- Close container tightly after application

SAFETY AND ENVIRONMENT

During Painting:

Always work in a well-ventilated area. Wear appropriate attire, especially gloves, eye protection and mask. Avoid contact with skin as it may cause irritation.

Cleaning:

Wash all tools with clean water immediately after application.

Safety Instructions:

In case of eye contact rinse immediately with water and seek immediate medical treatment. To remove the material from skin, use soap and water or appropriate cleanser. Safety datasheets will be made available to professional users upon request

Storage:

Store in a cool dry and well ventilated place away from heat sources, flammables or direct sun light. Do not store near food, drinks or animal feed. Keep out of reach of children.

Shelf Life:

Best before 1 year from date of manufacturing in unopened original packing when stored in dry condition.

