



NEROLAC SURAKSHA SHEEN EXTERIOR ACRYLIC EMULSION

NEROLAC

Colours that Care



PRODUCT DESCRIPTION

Nerolac Suraksha Sheen Plastic Exterior Emulsion is a water based exterior emulsion designed to impart best in class sheen and luxurious appearance to exterior walls along with long lasting performance. It is suitable for dry or moderately humid climatic conditions.

PERFORMANCE FEATURES & BENEFITS

| | | | |
|--|-----------------|---|---------------------------|
|  | Good Sheen |  | Good coverage |
|  | High durability |  | Algae & fungal resistance |
|  | Low VOC | | |

***As compared to normal cement paint. Applicable on certain shades only.

SURFACE PREPARATION

1. The surface to be painted must be free from all dust, grease, traces of paint flakes, algae and fungus.
2. The surface previously coated with paint must be cleaned thoroughly with a stiff wire brush to remove dirt, dust, chalking or loose flakes.
3. Wash thoroughly with water and allow to dry to ensure proper adhesion of the new paint system.
4. In case of fungus affected area, apply a liberal coat of Nerolac Fungicidal Solution.
5. Allow it to react for minimum of 6-8 h.
6. For parapet tops and other horizontal surfaces, application of 3 coats is recommended
7. All structural cracks must be opened in V shape filled with cement and sand mixture and leakage should be stopped before actual painting.
8. Freshly plastered surfaces must be allowed to cure completely for minimum of 12 weeks.

RECOMMENDED SYSTEM FOR APPLICATION:

1. Thin 1 L paint with maximum 600-700 ml of clean water.
2. Apply 2 to 3 coats with an interval of 4-6 h by brush or roller. Dark shade may require additional coat for hiding.
3. For horizontal surfaces and parapet tops application of 3 coats are required for better protection.

PRECAUTIONS

1. Refer MSDS of "Nerolac Suraksha Sheen Exterior Emulsion" for safety measures & precautions.
2. Store in well ambient conditions, ventilated locations & away from the source of ignition & fire.
3. Keep away from children.
4. In case of eye/skin contact, wash with plenty of water.
5. Inhalation/Injection is dangerous. In either case, move to fresh air & consult medical practitioners.
6. Do not apply when ambient temperature might drop to level below 10°C within 4 h of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results
9. Do not use universal strainers. Stir paint well before application.
10. The container must be tightly closed when not in use. Stir well and strain before use.
11. Use safety equipment's like rubber or polythene gloves, safety goggles/glasses & face mask.

TECHNICAL DATA



* Actual covering capacity may vary depending upon the method of application & condition of application, surface condition, temperature, wind velocity, application skills, surface roughness, surface porosity & shade.

POST APPLICATION INSTRUCTIONS

For the best performance of paint, ensure proper washing and cleaning of all algae and fungal growth at regular intervals of 6 months.

| | | | |
|--|--|--|---|
| | SAFETY FEATURES Non-Flammable | | PACK SIZE 1L, 4L, 10L & 20L. |
| | SHADE RANGE As per Colour Scapes Fandeck and shade card. | | NO. OF SHADES POSSIBLE More than 1200 |
| | SHELF LIFE 2 years from date of manufacture. | | |

DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products, therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement, prior to full-scale usage of our products.

The company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.